



Hohlstahl

DIN EN 10216-5

warmgewalzt oder stranggepresst und gebeizt

Toleranz: Iso 2938 – 1974

Werksabnahmezeugnis: EN 10204/3.1

- lieferbar

Hohlstahl
rostfrei und säurebeständig,
geglüht und gebeizt



Abmessung mm	Wandstärke mm	Gewicht kg / m	4301	4571
32,00 x 16,00	8,00	4,700	•	•
20,00	6,00	3,800	•	•
36,00 x 16,00	10,00	6,400	•	•
20,00	8,00	5,500	•	•
25,00	5,50	4,100	•	•
40,00 x 20,00	10,00	7,400	•	•
25,00	7,50	6,000	•	•
28,00	6,00	5,000	•	•
45,00 x 20,00	12,50	10,000	•	•
25,00	10,00	8,900	•	•
28,00	8,50	7,600	•	•
32,00	8,50	6,200	•	•
50,00 x 25,00	12,50	11,600	•	•
32,00	9,00	9,100	•	•
36,00	7,00	7,400	•	•
56,00 x 28,00	14,00	14,500	•	•
36,00	10,00	11,300	•	•
40,00	8,00	9,500	•	•
60,00 x 40,00	10,00	12,300	•	•
44,00	8,00	10,400	•	•
63,00 x 32,00	15,50	18,100	•	•
36,00	13,50	16,500	•	•
40,00	11,50	14,600	•	•
45,00	9,00	12,000	•	•
50,00	6,50	9,100	•	•
70,00 x 50,00	10,00	15,000	•	•
71,00 x 36,00	17,50	23,100	•	•
40,00	15,50	21,200	•	•
45,00	13,00	18,600	•	•
56,00	7,50	11,700	•	•
75,00 x 40,00	17,50	24,800	•	•
50,00	12,50	19,500	•	•
60,00	7,50	12,500	•	•
76,00 x 58,00	9,00	15,000	•	•
80,00 x 40,00	20,00	29,600	•	•
45,00	17,50	27,000	•	•
50,00	15,00	24,000	•	•
63,00	8,50	15,000	•	•
85,00 x 45,00	20,00	32,000	•	•
90,00 x 50,00	20,00	34,500	•	•
56,00	17,00	30,600	•	•
63,00	13,50	25,500	•	•
71,00	9,50	18,800	•	•

Hohlstahl
rostfrei und säurebeständig,
geglüht und gebeizt



Abmessung mm	Wandstärke mm	Gewicht kg / m	4301	4571
95,00 x 50,00	22,50	40,900	•	•
100,00 x 56,00	22,00	42,300	•	•
63,00	18,50	37,200	•	•
71,00	14,50	30,600	•	•
80,00	10,00	22,200	•	•
106,00 x 56,00	25,00	49,900	•	•
63,00	21,50	44,800	•	•
71,00	17,50	38,200	•	•
80,00	13,00	29,800	•	•
112,00 x 63,00	24,50	52,800	•	•
71,00	20,50	46,200	•	•
80,00	16,00	37,800	•	•
90,00	11,00	27,400	•	•
118,00 x 63,00	27,50	61,300	•	•
71,00	23,50	54,700	•	•
80,00	19,00	46,300	•	•
90,00	14,00	35,900	•	•
125,00 x 71,00	27,00	65,200	•	•
80,00	22,50	56,800	•	•
90,00	17,50	46,400	•	•
100,00	12,50	34,600	•	•
132,00 x 71,00	30,50	76,300	•	•
80,00	26,00	67,900	•	•
90,00	21,00	54,400	•	•
106,00	13,00	38,100	•	•
140,00 x 80,00	30,00	81,300	•	•
90,00	25,00	70,800	•	•
100,00	20,00	59,100	•	•
112,00	14,00	43,500	•	•
150,00 x 80,00	35,00	99,200	•	•
95,00	27,50	84,350	•	•
106,00	22,00	69,400	•	•
125,00	12,50	42,300	•	•
160,00 x 90,00	35,50	109,550	•	•
112,00	24,00	80,440	•	•
122,00	19,00	67,100	•	•
132,00	14,00	50,500	•	•
170,00 x 106,00	32,00	110,600	•	•
118,00	26,00	92,320	•	•
130,00	20,00	73,900	•	•
140,00	15,00	57,300	•	•
180,00 x 125,00	27,50	103,300	•	•
130,00	25,50	97,000	•	•

Hohlstahl
rostfrei und säurebeständig,
geglüht und gebeizt



Abmessung mm	Wandstärke mm	Gewicht kg / m	4301	4571
180,00 x 140,00	20,00	80,000	•	•
150,00	15,00	61,000	•	•
190,00 x 106,00	42,00	155,650	•	•
123,00	33,50	129,300	•	•
132,00	29,00	115,000	•	•
140,00	25,00	107,700	•	•
150,00	20,00	83,800	•	•
160,00	15,00	64,700	•	•
200,00 x 140,00	30,00	127,700	•	•
150,00	25,00	109,600	•	•
160,00	20,00	90,200	•	•
212,00 x 130,00	41,00	175,600	•	•
150,00	31,00	138,000	•	•
170,00	21,00	100,500	•	•
224,00 x 140,00	41,00	191,400	•	•
180,00	22,00	111,300	•	•
236,00 x 150,00	43,00	207,800	•	•
190,00	23,00	122,700	•	•
240,00 x 170,00	35,00	177,000	•	•
250,00 x 200,00	25,00	140,900	•	•